

RAC**NON-INVERTER**

Model		AS-09HR4SVDTE5	AS-12HR4SVETE2	AS-18HR4SXATE	AS-22HR4SBBTE
Type		Heat pump	Heat pump	Heat pump	Heat pump
Cooling Capacity	W	2640	3520	5384	6531
Heating Capacity	W	2655	3590	5340	6448
Refrigerant		R410A	R410A	R410A	R410A
Refrigerant volume	g	640	920	1460	1580
Indoor Unit Noise Level	High (dB)	38	39	43	45
	Low (dB)	34	35	38	40
Outdoor Unit Noise Level	dB	53	55	54	55
Voltage, Frequency, Phase		220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V~,50Hz,1P
Net Dimensions WxHxD (mm)	Indoor Unit	780×270×202	850×270×202	960×315×235	1131×315×235
	Outdoor Unit	715×482×240	715×482×240	810×585×280	860×650×310
Net Weight (Kg)	Indoor Unit	8	8,5	12,5	14,5
	Outdoor Unit	26	29	40,5	47
Packing Dimensions WxHxD (mm)	Indoor Unit	830×335×260	900×335×260	1022×380×302	1220×400×310
	Outdoor Unit	830×530×315	830×530×315	940×630×385	995×730×445
Gross Weight (Kg)	Indoor Unit	9,5	11	15,5	17
	Outdoor Unit	28	31,5	45	51
Liquid Pipe		1/4	1/4	3/8	3/8
Gas Pipe		3/8	1/2	5/8	5/8
Loading Capacity (20'/40'/40'HC) without pipe		148/298/345	140/285/335	86/180/201	60/128/144
Loading Capacity (20'/40'/40'HC) with pipe		135/281/332	134/280/320	86/180/201	60/128/144

Remarks:

The design and specifications are subject to change without prior notice for product improvement.

The values given in the table for noise level reflect the levels in anechoic chamber.